

Multi Overview



# Multi

---

*α*

# Introduction

A technical luminaire that, thanks to its outstanding lighting properties and good looks, has endless application opportunities – hence the name!

IP65 industrial LED luminaire with a specialised optical system for improved performance and visual comfort. cost-effective, low-maintenance and low-glare design minimises shadowing and delivers multiple benefits to the client and occupants. Fully surface mounted with smooth vertical-sided housing for Primary Industry applications.


## Applications:

- Carpark entries and transition zones
- Gas station canopies
- Loading docks
- General industrial
- Multi purpose/indoor sports
- Food preparation areas
- Cool Rooms
- Cold Rooms
- Workshops

## Unique Features:

- Uses Architech's unique faceted refractor for outstanding light output, low-glare properties and broad distribution.
- IP65 construction for wet, cold or humid environments.
- Integrated pressure compensation filter eliminates condensation and contaminants.
- Shallow profile to suit lower mounting heights.
- Available with MelaGen® Blue.
- Comes surface mounted as standard, option for suspension kit.

Multi



Design

Low-profile, extruded, rolled and welded aluminium housing, sealed and powder coated white. Aluminium body and backplate with unique 'twist and lock' mounting method for simple installation, including IP68 cable entry gland and integrated cord grip.

Lens Options

Sealed acrylic lens for high quality, low glare illumination

IK10 Polycarbonate lens available for non-food applications, and applications where impact may be a concern

Beam Angle

Broad distribution

Colour Temperature

4000K CRI80 as standard  
4200K MelaGen Blue CRI90

Control Options


Fixed output driver  
DALI dimmable driver  
Integrated microwave motion sensor option

Electrical


Wattage 75W - 150W

Outputs

Up to 25,000lm fixture output  
> 164lm/W efficacy




Polar Curve



Multi Optic

Photometry from MULTIMA.0675xx.4080A.1



# Multi Specification



# The Multi Range

Specifying a Multi can be done by listing the variations as per below:

Product Name | Lens . Output | Control . CCT | CRI | REF . Finish . Optional (If needed)

Standard Combinations Table		MULTI	Code
		MULTIM	
● Standard Offering      ○ No Cost Option      + Adder Option			
Lens	Acrylic	●	A
	Polycarbonate	○	P
Output	350mA	●	0350
	500mA	○	0500
	675mA	○	0675
Control	Fixed	●	F0
	DALI Dimmable	+	DD
CCT	4000K	●	40
	MelaGen® Blue (Ra90 only)	+	BL
CRI	Ra80	●	80
	Ra90	○	90
Internal Reference		●	A
Finish	White	●	1
Sensor (optional)	Fixed Output Integrated Microwave Sensor (add suffix)	+	FMS
	DALI Integrated Microwave Sensor (DALI only, add suffix)	+	DMS


Accessory: Suspension bracket + eyebolt with flex

Code: MULTIM.SB.EBF

Example Sales Reference: **MULTIMA.0350F0.4080A.1**  
Description: **MULTI** Acrylic **350mA** **Fixed** Output **4000K** **Ra80** Internal reference (**A**)  
White (**1**)

PRODUCT	WATTAGE	LUMENS
MULTIMA.0350xx.4080A.1	75W	12,800lm
MULTIMA.0500xx.4080A.1	110W	18,300lm
MULTIMA.0675xx.4080A.1	150W	24,600lm
MULTIMP.0350xx.4080A.1	75W	11,900lm
MULTIMP.0500xx.4080A.1	110W	16,900lm
MULTIMP.0675xx.4080A.1	150W	22,800lm

Accessory: Suspension bracket + eyebolt with flex.  
Use code to order: MULTIM.SB.EBF



---

**HEAD OFFICE**

Via Simone Schiaffino, 11/19

20158 Milano

Tel. +39 02 36591961

Tel. +39 02 36591979

[enquiries@architech.lighting](mailto:enquiries@architech.lighting)

*α*